Catalog

SPA-200-2E.pdf ·····	···· 1
SPA-200-4E.pdf ·····	
SPA-250-2E.pdf ·····	3
SPA-250-4E.pdf ·····	•••• 4
SPA-300-2E.pdf ·····	
SPA-300-4E.pdf ·····	6
SPA-350-4E.pdf ·····	7



SPA200-2E


SQUARE PLATE AXIAL FANS

FAN FEATURES

- SQUARE PLATE AXIAL FAN. CAPABLE OF HANDLING UP TO 220 L/s.
- USED FOR TOILET EXHAUST AND GENERAL VENTILATION.
- SPEED CONTROLLABLE.
- CIRCULAR CONNECTION
- FULL COMPLIANCE WITH AUSTRALIAN STANDARDS AIRFLOW TEST TO BS848
 PART 1 & NOISE TEST TO BS848 PART 2

DIMENSIONS

PERFORMANCE





SOUND DATA

	Octave Band Frequency Lw db (A)									
Model	63	125	250	500	1K	2K	4 K	8K		
SPA200-2E		42	55	58	60	61	58	51	66	44

TECHNICAL DATA

Fan Model	RPM	1 Phase KW	240V Amps	3 Phase KW	415V Amps	dba @3M
SPA-200-2E	2550	0.07	0.30			44



ECO DYNAMIC FANS PTY LTD



SPA200-4E


SQUARE PLATE AXIAL FANS

FAN FEATURES

- SQUARE PLATE AXIAL FAN. CAPABLE OF HANDLING UP TO 132 L/s.
- USED FOR TOILET EXHAUST AND GENERAL VENTILATION.
- SPEED CONTROLLABLE.
- CIRCULAR CONNECTION
- FULL COMPLIANCE WITH AUSTRALIAN STANDARDS AIRFLOW TEST TO BS848
 PART 1 & NOISE TEST TO BS848 PART 2

DIMENSIONS

PERFORMANCE





SOUND DATA

		Lw dB (A)	SPL dB (A) @3m							
Model	63	125	250	500	1K	2K	4 K	8K		
SPA200-4E		35	38	44	45	44	39	27	49	28

TECHNICAL DATA

Fan Model	RPM	1 Phase KW	240V Amps	3 Phase KW	415V Amps	dba @3M
SPA-200-4E	1390	0.032	0.15			28



ECO DYNAMIC FANS PTY LTD



SPA250-2E


SQUARE PLATE AXIAL FANS

FAN FEATURES

- SQUARE PLATE AXIAL FAN. CAPABLE OF HANDLING UP TO 445 L/s.
- USED FOR TOILET EXHAUST AND GENERAL VENTILATION.
- SPEED CONTROLLABLE.
- CIRCULAR CONNECTION
- FULL COMPLIANCE WITH AUSTRALIAN STANDARDS AIRFLOW TEST TO BS848
 PART 1 & NOISE TEST TO BS848 PART 2

DIMENSIONS

PERFORMANCE





ww.ecodynamicfans.com.au

SOUND DATA

			Octav	ve Band Fr	equency	Lw db (A)			Lw dB (A)	SPL dB (A) @3m
Model	63	125	250	500	1K	2K	4 K	8K		
SPA250-2E		46	62	68	67	66	64	57	73	51

TECHNICAL DATA

Fan Model	RPM	1 Phase KW	240V Amps	3 Phase KW	415V Amps	dba @3M
SPA250-2E	2650	0.123	0.54			51



ECO DYNAMIC FANS PTY LTD

w



SPA250-4E


SQUARE PLATE AXIAL FANS

FAN FEATURES

- SQUARE PLATE AXIAL FAN. CAPABLE OF HANDLING UP TO 290 L/s.
- USED FOR TOILET EXHAUST AND GENERAL VENTILATION.
- SPEED CONTROLLABLE.
- CIRCULAR CONNECTION
- FULL COMPLIANCE WITH AUSTRALIAN STANDARDS AIRFLOW TEST TO BS848
 PART 1 & NOISE TEST TO BS848 PART 2

DIMENSIONS

PERFORMANCE





SOUND DATA

	Octave Band Frequency Lw db (A)									
Model	63	125	250	500	1K	2K	4 K	8K		
SPA250-4E		41	47	50	51	52	47	36	57	36

TECHNICAL DATA

Fan Model	RPM	1 Phase KW	240V Amps	3 Phase KW	415V Amps	dba @3M
SPA250-4E	1315	0.054	0.25			36



ECO DYNAMIC FANS PTY LTD



SPA300-2E


SQUARE PLATE AXIAL FANS

FAN FEATURES

- SQUARE PLATE AXIAL FAN. CAPABLE OF HANDLING UP TO 780 L/s.
- USED FOR TOILET EXHAUST AND GENERAL VENTILATION.
- SPEED CONTROLLABLE.
- CIRCULAR CONNECTION
- FULL COMPLIANCE WITH AUSTRALIAN STANDARDS AIRFLOW TEST TO BS848
 PART 1 & NOISE TEST TO BS848 PART 2

DIMENSIONS

PERFORMANCE





SOUND DATA

			Octav	ve Band Fr	equency	Lw db (A)			Lw dB (A)	SPL dB (A) @3m
Model	63	125	250	500	1K	2K	4 K	8K		
SPA300-2E		55	64	74	73	73	70	62	79	58

TECHNICAL DATA

Fan Model	RPM	1 Phase KW	240V Amps	3 Phase KW	415V Amps	dba @3M
SPA300-2E	2505	0.21	0.9			58



ECO DYNAMIC FANS PTY LTD



SPA300-4E


SQUARE PLATE AXIAL FANS

FAN FEATURES

- SQUARE PLATE AXIAL FAN. CAPABLE OF HANDLING UP TO 500 L/s.
- USED FOR TOILET EXHAUST AND GENERAL VENTILATION.
- SPEED CONTROLLABLE.
- CIRCULAR CONNECTION
- FULL COMPLIANCE WITH AUSTRALIAN STANDARDS AIRFLOW TEST TO BS848
 PART 1 & NOISE TEST TO BS848 PART 2

DIMENSIONS

PERFORMANCE





SOUND DATA

			Octav	ve Band Fr	equency	Lw db (A)			Lw dB (A)	SPL dB (A) @3m
Model	63	125	250	500	1K	2K	4 K	8K		
SPA300-4E		46	53	54	55	55	51	39	60	39

TECHNICAL DATA

Fan Model	RPM	1 Phase KW	240V Amps	3 Phase KW	415V Amps	dba @3M
SPA300-4E	1280	0.096	0.43			39



ECO DYNAMIC FANS PTY LTD



SPA350-4E


SQUARE PLATE AXIAL FANS

FAN FEATURES

- SQUARE PLATE AXIAL FAN. CAPABLE OF HANDLING UP TO 925 L/s.
- USED FOR TOILET EXHAUST AND GENERAL VENTILATION.
- SPEED CONTROLLABLE.
- CIRCULAR CONNECTION
- FULL COMPLIANCE WITH AUSTRALIAN STANDARDS AIRFLOW TEST TO BS848
 PART 1 & NOISE TEST TO BS848 PART 2

DIMENSIONS

PERFORMANCE





SOUND DATA

	Octave Band Frequency Lw db (A)							Lw dB (A)	SPL dB (A) @3m	
Model	63	125	250	500	1K	2K	4 K	8K		
SPA350-4E		48	56	62	64	65	63	54	69	48

TECHNICAL DATA

	Fan Model	RPM	1 Phase KW	240V Amps	3 Phase KW	415V Amps	dba @3M
SPAS	350-4E	1385	0.16	0.76			48



ECO DYNAMIC FANS PTY LTD